

Double Glider Unit Elevations

	41 $\frac{1}{8}$ "	49 $\frac{7}{8}$ "	57 $\frac{7}{8}$ "	65 $\frac{7}{8}$ "	73 $\frac{7}{8}$ "
Primed Unit Dimension	39 $\frac{3}{4}$ "	47 $\frac{3}{4}$ "	55 $\frac{3}{4}$ "	63 $\frac{3}{4}$ "	71 $\frac{3}{4}$ "
Rough Opening	39 $\frac{3}{4}$ "	47 $\frac{3}{4}$ "	55 $\frac{3}{4}$ "	63 $\frac{3}{4}$ "	71 $\frac{3}{4}$ "
Frame	16"	20"	24"	28"	32"
Glass					

23 $\frac{15}{16}$ "					
27 $\frac{7}{16}$ "					
31 $\frac{15}{16}$ "					
35 $\frac{15}{16}$ "					
39 $\frac{15}{16}$ "					
43 $\frac{15}{16}$ "					
47 $\frac{15}{16}$ "					
55 $\frac{15}{16}$ "					

Unit Dimension given for primed units only





















Clad unit dimension width is identical to frame width. Clad unit dimension height is $\frac{1}{4}$ " less than frame height.

Masonry Opening: Recommended minimum of Unit Dimension plus $\frac{1}{4}$ ". Due to the side jamb sill wedges, the clad vertical exterior unit dimension is $\frac{1}{4}$ " smaller than the frame height. This may affect masonry framing.

Shaded units meet UBC egress codes (5.7 sq. ft., 20" width, 24" height minimum) in standard 6'10" header application

Triple Glider Picture Unit Elevations

	74 ¹¹ / ₁₆ "	86 ¹¹ / ₁₆ "	90 ¹¹ / ₁₆ "	106 ¹¹ / ₁₆ "
Primed Unit Dimension	72 ¹ / ₂ "	84 ¹ / ₂ "	88"	104 ¹ / ₂ "
Rough Opening	72"	84"	88"	104"
Frame	16/32/16	20/36/20	20/40/20	24/48/24
Glass				

31 ¹ / ₁₆ "	30 ⁵ / ₁₆ "	30 ¹ / ₈ "	24"				
39 ⁷ / ₁₆ "	38 ⁵ / ₁₆ "	38 ¹ / ₈ "	32"				
43 ¹⁵ / ₁₆ "	42 ⁵ / ₈ "	42 ¹ / ₄ "	36"				
47 ¹⁵ / ₁₆ "	46 ⁵ / ₈ "	46 ¹ / ₄ "	40"				
55 ¹ / ₁₆ "	54 ⁵ / ₈ "	54 ¹ / ₄ "	48"				

Unit Dimension given for primed units only

Clad unit dimension width is identical to frame width. Clad unit dimension height is 1/4" less than frame height.

Masonry Opening: Recommended minimum of Unit Dimension plus 1/4". Due to the side jamb sill wedges, the clad vertical exterior unit dimension is 1/4" smaller than the frame height. This may affect masonry opening.

Shaded units meet UBC egress codes (5.7 sq. ft., 20" width, 24" height minimum) in standard 6'10" header application